



曲线元素表

交点号	交点坐标		交点桩号	转角值	曲线要素值(米)					
	X(N)	Y(E)			半径	缓和曲线长	切线长度	曲线长度	外距	校正值
JD83	4940909.292	716268.331	K4+981.434	6°27'17.2"(Y)	280		15.789	31.544	0.445	0.033
JD84	4940888.026	716283.632	K5+007.600	13°27'49.1"(Z)	88.194		10.410	20.724	0.612	0.096
JD85	4940843.057	716335.728	K5+076.324	20°19'05.2"(Y)	100		17.919	35.462	1.593	0.376
JD92	4940798.620	716360.238	K5+126.695	2°03'24.2"(Y)	700		12.565	25.128	0.113	0.003
JD86	4940762.137	716378.687	K5+167.575	17°39'13.6"(Z)	80		12.423	24.649	0.959	0.197
JD87	4940719.594	716420.461	K5+227.002	4°49'58.2"(Y)	400		16.880	33.739	0.356	0.020
JD95	4940699.181	716437.375	K5+253.492	11°15'05.2"(Z)	97.766		9.630	19.199	0.473	0.062
JD96	4940685.285	716454.472	K5+275.462	21°18'33.7"(Y)	65.92		12.402	24.517	1.156	0.287
JD96	4940663.963	716466.578	K5+299.694	34°25'24.7"(Z)	39.115		12.117	23.500	1.834	0.733
JD88	4940652.050	716491.015	K5+326.147	30°31'28.9"(Y)	55.226		15.069	29.422	2.019	0.716
JD89	4940617.833	716513.651	K5+366.457	27°28'26"(Y)	30		7.334	14.385	0.883	0.282
JD100	4940600.602	716515.465	K5+383.501	18°20'43"(Z)	61.883		9.993	19.814	0.802	0.171
JD90	4940564.931	716531.614	K5+422.486	16°07'49.3"(Z)	80		11.336	22.522	0.799	0.150
JD91	4940528.129	716563.033	K5+470.726	29°09'40.3"(Y)	60		15.607	30.538	1.997	0.677
JD103	4940487.370	716571.197	K5+511.618	7°02'05.1"(Z)	291.683		17.929	35.813	0.550	0.045
JD92	4940456.512	716581.439	K5+544.086	16°35'46.3"(Y)	100		14.585	28.966	1.058	0.204
JD105	4940416.065	716582.685	K5+584.348	4°42'55.2"(Y)	250		10.293	20.575	0.212	0.012

注：  
 1: 比例1:2000。  
 2: 平面坐标系采用国家2000坐标系，中央子午线81°。